THE ICHHAMATI CO-OPERATIVE MILK PRODUCERS UNION LTD.

HATIPUKUR ROAD, BARASAT-700124, NORTH 24 PARGANAS

PH NO-033-2562-2688, FAX NO-033-2552-1019, email-ichhamati123@yahoo.com

Ref no: - IMUL: Tender: IDDP: 385

Date-11-09-13

TENDER

The Ichhamati Co-operative Milk Producers' Union Ltd. is a Anand Pattern District level co-operative Society which is functioning under leadership of District Magistrate, North 24 Parganas. This Milk Union is inviting sealed quotation for purchase and installation of 1 no 'Walking Cold Store (10,000 lt. Capacity)' for milk chilling. For details specification/ description of IBT Unit is as under:-

	ANNEXTURE - 1	BASIS OF DESIGN	
LNa.	Description	Cold Storage for 10,000Lts/Kg	
		R-404A	
1	Refrigerant	20 x 12 x 8 5 (H)	
2)	Nominal Room Size in [External]		
G.	Capacity	10000 Lirs/Kgs Lassi, Butter, Cream etc. 1000 crate 0 Deg C	
1)	Room Temperature	0 Deg C ^{et} To -5 Deg. C	
5)	Ambient Temperature	42 Deg C*	
(i)	Product	Lassi, Butter, Cream . Milk etc	
71	Total Products Capacity in Crates	1000 Crates	
8)	Daily Product Load	10000 Liss.	
9)	Product incoming Temp.	+5 Deg C* To +6 Deg C*	
10)	Pull Down Tittle	14-18 Hours.	
11)	Waii and Ceiling Insulation	60 mm this PUF Panel	
12)	Floor Insulation	60 mm thk PUF Sinb insulation With tow layer vapor barrier [1.5 inc PCC with 25 mm Kota/mandona Stone Finish]	
13)	Door Size [Hinged Type]	78" x 34" x 50mm Thik	
14)	No. of Machines / Room	Two - I working > I partial standby	
[5]	No. of Rooms	One	
16)	System Type	Air Cooled	
17)	Required Refrigeration Capacity	24,100 BTUH	
18)	Offered Refrigeration Capacity	15,100 BTUH X 2 SETS	
19)	Inside Light Fittings	2 Sets Vapor Proof (CFL)	



the transfer of the second state of the second	
ANNEXTURE - 11	SCOPE OF SUPPLY

SLNo.	Description	Quantity
1)	BLUE STAR make Air Cooled Unit Refrigerant - R – 404A Model : RUAM – 01512DP + ZX030E	2 Sets
2)	Design and Supply of BLUE STAR make COLD STORAGE of as per dimension Having following specifications:- walls and ceiling 60mm PUF Panel with 24SWG Prepainted Sheet finish inside & outside. With Cambock arrangement	1 Set
3)	BLUE STAR make 60mm PUF Door Fully Flush-in type with Self Closing Posi-seal closure, Door Heater, Digital Thermometer, Sweep gasket, Full imported hard-wares. Built-in magnetic neoprene gasket, In-built human safety lever inside	1 Set
4)	BLUE STAR make 60mm thk PUF Slab insulation with two layer vapor barrier for Flooring	1 Set
5)	BLUE STAR make 60mm U Profile for Wall Panel standing	Lot
6)	BLUE STAR make Hatch Channel for Ceiling Panel suspension	Lot
7)	BLUE STAR approved Vapor Proof [CFL]	2 Sets
8)	BLUE STAR approved PVC Strip Curtain	1 Set
9)	Copper Refrigeration Piping and Fittings with necessary supports	2 Sets
10)	Suction line insulation with Nitrile Rubber	2 Sets
11)	DANFOSS / Equivalent make Refrigeration Controls comprising of the following. Thermostatic Expansion Valves Solenoid Valves Sight Glasses Filter Driers Ball Valves	2 Sets
2)	First Charge of R - 404A Gas and Compressor Oil	2 Sets
13)	Complete Supports for Equipments	2 Sets
14)	PVC Drain Pipes to drain out the Condensate from the Evaporator outlet to the nearest drain Pit	2 Sets



f heat Transfer sulation uctivity strength		BLUE STAR Ltd CFC free Foamed in-place POLY URETHENE FROM (PUF) 0.366 W/M-C 40 + :-2 kg/m3		
sulation		CFC free Foamed in-place POLY URETHENE FROM (PUF) 0.366 W/M-C 40 + 2-2 kg/m3		
sulation		PUF) 0.366 W/M-C 40 + /-2 kg/m3		
sulation		40 + / -2 kg/m3		
uctivity				
uctivity				
		<0.02 kcal/m2, hr. C		
strength		<0.02 kcal/m2. hr. C		
		1.3 kg/cm2 (min)		
ngth(PUF to steel)		150 PSI		
ontents		95% (min)		
Fire resistance		Will not sustain fire in absence of source		
Water absorption		2% (max)		
Vapour permeability		Less then 2%		
Vapour permeaning Thickness of outer sheets		24 Gauge		
		Prepainted Gl		
Material of outer sheets				
Amount of Zinc Coating		120 GSM or above		
Type of camlock for panel locking		Metallic		
Type of sealant		Gasket/silicone		
ly R- 141 blown foar	n at 32-36Kgs/Cubic Mtr.	Yes		
ability within 2% after	er 48 Hrs. of foaming	Yes		
Radiused will to impede bacterial growth		Yes		
Panel joints		With double vinyl gasket & metallic Cam Lock (Pre- fabricated with the panels to make leak proof joints). Or floor, U-profile will be grouted for holding wall panel- and ensuring anti-dampness.		
urer		BLUE STAR Ltd		
	78" x 34	78" x 34" x 60 mm- Thk		
res	Positive C Vinyl gast Safety Rei	Hydraulic Door Closure Positive Cam Lift Hardware Vinyl gasket on all sides & with SS brackets at the bottom of door Safety Release Exit device for opening door from inside Door Heater		
tes		Hydraulic Positive C Vinyl gask Safety Rei		

Madaging Director Ichhamati Milk Union